www.wonderfloor.co.in

WONDERFLOOR

Stoneland Monza

PUR MADE INDIA

Luxury Vinyl Tiles

Stoneland Monza

Application areas Hotels, Offices, Houses, Schools Commercial buildings and Retail Spaces etc.



STN 01



STN 03



STN 02



STN 04














STN 09



STN 11




STN 10



STN 12







STN 05



STN 07



STN 06



STN 08



maintenance costs



Design Film

The design film made of the most popular style is used as a decoration for the floor

PVC Base

The technology to maintain the floor stability



RFLOOR - The world-class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2015 systems certified company. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in state-of-the art plant & machinery equipped with latest technology and optimum quality control. Wonderfloor has a wide sales distribution network across India.

ONZA are the latest collection of PVC stone tiles. The shades and designs are carefully chosen to complement the natural stone Manufactured with multi-layer technology, this premium flooring is highly suitable to handle heavy footfalls. The PUR protection layer ensures trouble free performance and enhance durability. Stoneland Monza reduces noise impact, is trendy, quick to install, easy to use and maintenance free. Finally, these are termite resistant, moisture resistant & fire resistant. Stoneland Monza tiles are recommended for hotels, stores, malls, cafeteria. auditorium, schools, banks, offices etc.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	STONELAND MONZA
TYPE OF FLOORING	EN 649	RESILIENT FLOORING
THICKNESS (mm)	EN 428	2.0 mm*
DIMENSION (SIZE)	EN 427	457.2mm X 457.2mm (18" X 18")**
SQAURENESS	IS: 3464	≤ 0.25 mm
WEAR LAYER		0.20 mm (Heavy duty)
DENSITY	EN 430	3500g/m²
DIMENSIONAL STABILITY	EN 434	≤ 0.25 mm
RESIDUAL INDENTATION	EN 433	≤ 0.10 mm
FLEXIBILITY	EN 435	NO CRACKING USING 20mm mandrel
COLOR FASTNESS	ISO 105 B02	CLASS 6
FIRE RATING	EN 13501 - 1	Bff-S1
HORIZONTAL & VERTICAL BURNING TEST	IS 15061 - 2002	PASS (ARAI)
PERFORMANCE CLASSIFICATION	EN 685	34/41
ABRASION RESISTANCE	EN 660-2	Wear Group P
SOUND ABSORPTION	ISO 140-8/EN 1SO 717-2	ΔLW=5db
SLIP RESISTANCE	DIN 51130	R9
BEARING CASTOR CHAIR	EN 425	SUITABLE / CONTINUOUS USE
SURFACE PROTECTION	PUR	PUR
MOISTURE MOVEMENT	APPENDIX B OF IS: 3462	≤ 0.40%
RESISTANCE TO STAINING	EN 423	PASS
PATTERN		STONE
PACKING DETAILS		20 pcs / box = 4.18 sqm / box (45 sq.ft)

*Thickness: 1.5 mm / 3.0 mm can be produced against bulk quantity orders. **Tile_sizes: 300 mm x 300mm / 228.60 mm x 914.40 mm can be produced against bulk quantity orders.

land Monza must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl tiles are suitable for laying on any surface such as concrete, steel and floor sets. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, of the floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, of the floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, of the floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, of the floor is even, hard and dry. Damp floors should be dried before the commencement of laying.

condension premium flooring range are UV cured with PUR guard for resistance against stains and scratches in addition to minimising the maintenance cost. A light mop daily will keep corings spick & span, if required. A door mat if placed at the entrance of the room will ensure that dust particles remain out which will further enhance the aesthetic look and ensure a long race life of the flooring.

After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution. Prevent point load indentation by covering your furniture legs thrubber stopper caps. To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution. Scuff marks on the floor and removed with little application of diesel. Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring. Use water to remove any chemical spill on flooring.

• Do not use any strong detergent, harsh cleaning agent or dry steel wool. Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn arks on the floor.

For institutional/bulk enquiries, please e-mail: mkt@rmgpoly.com or call: +91 9711200510
For export enquiries, please e-mail: info@rmgpoly.com or call: +91 9873138885 / +91 9953208740









RMG POLYVINYL INDIA LIMITED

rporate Office :UGSR 4, Ansal Plaza, Sector 1, Valshali Ghazlabad 201 010. (U.P) INDIA Tel.: +91 120-4284802/803/804/805/806. Fax: +91 11 66173679

E-mail: info@rmgpoly.com
- Ahmedabad: 9377262959 - Bangalore: 8088083037 - Bhubaneswar: 9582624009 - Chandigarh: 9023363357 - Chennal: 9380353335 - Guwahati: 9999014098
- Ahmedabad: 9377262959 - Bangalore: 8088083037 - Bhubaneswar: 9582624009 - Chandigarh: 9023363357 - Chennal: 9380353335 - Guwahati: 9399014098
- Hyderabad: 9953724744 - Indore: 7838590904 - Kolkata: 9582538009 - Kochi: 8893191421 - Lucknow:9026708007 - Mumbal: 9323675979 - Patna: 8252110100
- Pune: 9595191421 - Raipur: 9582431919

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited



